

JTR-H



Green Power

WEED CONTROL
system



NEW
POWERSTEAM
system



European homologation - Approved for road transport, 1050 kg or 1500 kg GVW.
Omologazione Europea - Omologato per il trasporto stradale, 1050 kg o 1500 kg di GVW massimo.



Automatic-winding HP hose reel (versions up to 350 bar) or manual (500 bar versions)

Naspo HP ad avvolgimento automatico (versioni fino a 350 bar) o manuale (versioni 500 bar)



Heavy duty single axle trailer complete with high load capacity tires

Rimorchio monoasse per utilizzi gravosi completo di pneumatici ad elevata capacità di carico



JTR-H 23/350

JTR-H 30/500



Single boiler with anti-scale device and tank

Singola caldaia con dispositivo anticalcare e serbatoio



Front and rear cover and watertank in Fiberglass

Copertura anteriore e posteriore e serbatoio dell'acqua in vetroresina



PLC control panel

Pannello di controllo PLC



GENERAL FEATURES · CARATTERISTICHE GENERALI

- Single axle trailer with rear lights and reflectors, automatic reverse gear, parking brakes, high load tyres, ABS and Mudguards
- Towing eye for a 50 mm diam. Sphere type
- 600 l water tank with low level alarm
- Water cooled Yanmar or Kohler diesel engine with electric starter
- Manual throttle control (Automatic on 30/500)
- RW/TW Comet pump with pulley and belt transmission or reducer
- Pressure gauge, pressure regulator, safety valve and manual throttle (automatic on 30/500 model)
- Manual hose reel 500 bar high pressure version: 50m-1/2" or 3/8"; 350 bar automatic version: 30m-3/8" or 1/2"
- Manual hose reel with 35m hose for refill
- Front/Rear hoods and watertank of 600l capacity in Fiberglass
- Diesel (single or twin) heater with electronic temperature control system and anti-scale device
- High pressure hose max 20m or 50m 3/8 "(optional)
- Working light (optional)
- Carrello monoasse con luci posteriori e riflettori, retromarcia automatica, freno di stazionamento, pneumatici per carichi elevati, ABS e parafanghi
- Occhiello sferico di traino diametro 50 mm
- Serbatoio acqua 600 litri con allarme livello minimo
- Motore diesel Kohler o Yanmar raffreddato ad acqua, con avviamento elettrico
- Acceleratore di giri manuale (Automatico su 30/500)
- Pompa Comet RW/TW trasmissione a cinghia e puleggia o riduttore
- Manometro, regolatore di pressione, valvola di sicurezza e acceleratore manuale (automatico sul modello 30/500)
- Avvolgitubo alta pressione versione 500 bar manuale: 50m-1/2" or 3/8"; 350 bar versione automatico: 30m-3/8" o 1/2"
- Avvolgitubo manuale con tubo da 35 m per ricarica
- Cofanature anteriori / posteriori e serbatoio d'acqua di capacità 600l in vetroresina
- Caldaia diesel (singola o doppia) con sistema elettronico di controllo della temperatura e dispositivo anticalcare
- Tubo alta pressione max 20m o 50m 3/8 "(optional)
- Faro di lavoro (optional)



TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

MODELS MODELLI	l/min	bar	type	HP	kW	600 lt cm (L x W x H)	kg
JTR-H 21/200	21	200	Kohler	17	12,6	337x164x154	≥ 900
JTR-H 23/350 T	23	350	Kohler	26	19	337x164x154	≥ 900
JTR-H 23/350	23	350	Kohler	26	19	337x164x154	≥ 900
JTR-H 30/500	30	500	Yanmar	48	35,5	337x164x154	≥ 900

ACCESSORIES ON REQUEST · ACCESSORI A RICHIESTA

<p>Gun kit with different type of cleaning lances Kit pistola con varie tipologie di lance da lavaggio</p>	<p>M24x1,5 floorwash kit Kit lavapavimenti M24x1,5</p>	<p>Hydrosandblasting kit Kit per idrosabbatura</p>	<p>Lancia a vapore per diserbo angolata e carrellata Bent and Wheeled weed killer steam lance</p>
--	--	--	---